



PRODUCT INFORMATION

November 2015

6820HDN / 6820HDS

68L Mobile Diesel Transfer Tank with Rotary Pump & Nozzle (6820HDN) or Spout (6820HDS)

The 6820HDN 68L mobile diesel transfer tank with rotary vane pump and nozzle and the 6820HDS 68L mobile diesel transfer tank with rotary vane pump and spout are ideal for transporting diesel to perform refuelling of small vehicles, workshop & farm equipment, agricultural/landscaping tools and recreational vehicles or crafts.

Featuring a unique design with ergonomic grip for ease of handling and lifting, the tank is equipped with solid 8" PU wheels suitable for mobility on any surface.

The tank is manufactured in roto-molded linear polyethylene, is impact resistant, UV stabilised and fitted with a filling plug complete with integrated air vent device and a lower safety tap.

Supplied standard with a manual rotary vane pump (flow rates of up to 50L/min), manual nozzle (6820HDN) or spout (6820HDS) and 3m of delivery hose.

Please note that the pump must be thoroughly washed, cleaned and free of AdBlue® internally after each use. AdBlue® when in contact with air will bind the internals and may break the pump, voiding manufacturer and Alemlube warranties.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Tank capacity 68 litres

Flow rate of up to 50 L/min

Rotary vane pump

Plastic nozzle (F20040) Spout (6820HDN)

Ergonomic grip for ease of handling and lifting

Solid 8" PU wheels suitable for mobility on any surface.

Roto-molded linear polyethylene tank - impact resistant, UV stabilised

PVC hose delivery 3/4"

2" filling plug with integrated air vent device

Lower safety tap

3 metres of delivery hose

Dimensions: 980mm (H) x 500mm (L) x 400mm (W)

Weight: 11kg

ORDERING INFORMATION:

6820HDN / 6820HDS 68L Mobile Diesel Transfer Tank with Rotary Pump & Nozzle or Spout

