



PRODUCT INFORMATION

JUNE 2018



DK80

Alemlube Diesel Driven 3" Diesel & Water Transfer Engine Pump Key Start

The Alemlube DK80 diesel driven 3" transfer engine pump is specifically designed and manufactured for the transfer of diesel and water. Mounted in a robust tubular steel roll frame with rubber feet the DK80 is completely portable, suits many industrial, workshop, agricultural, municipal, marine services and on site applications including construction site dewatering and is capable of transferring up to 900 litres of diesel fuel or water per minute.

Driven by a powerful diesel engine this lightweight die-cast aluminium pump with 3" diameter inlet & outlet ports operates efficiently with a maximum suction head of 7 metres and a maximum lift head of 26 metres. Always ready to perform tank filling, diesel or water transfer the DK80 has a 3.5L fuel tank capacity with a key start starting system.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

- Flow rates of up to 900L/min
- 6.0HP (3,600rpm) air cooled 4-stroke diesel engine
- 3" (80mm) inlet/outlet
- Maximum suction head of 7m
- Maximum lift head of 26m
- Fuel tank capacity of 3.5L
- Oil tank capacity of 1.1L
- Completely portable with key start

ORDERING INFORMATION

DK80 Alemlube Diesel Driven 3" Diesel & Water Transfer Engine Pump Key Start

