



PRODUCT INFORMATION

October 2017 Update

48010 Tyre and Wheel Lifting & Handling Trolley

The Alemlube 48010 tyre and wheel lifting & handling trolley is a fully pneumatic automatic wheel lifter designed for use in automotive workshops and professional tyre service workshops.

Manual lifting of wheels off and onto vehicles is the most common cause of stress and injury in the vehicle service industry.

The 48010 significantly reduces this hazard by facilitating quick and easy removal and handling of car & light commercial vehicle wheels resulting from smart and functional design.

Simply operated by two buttons on the trolley handles, the wheel platform equipped with stainless steel rollers is raised to allow perfect alignment of the wheel and wheel hub, then lowers the wheel to a workable height for the wheel to be transferred to the Wheel Transport Trolley (supplied with the 48010). Reducing manual handling, this labour saving device makes working with wheels and tyres extremely OH&S friendly and results in greater efficiency and productivity.

The 48010 is manufactured from durable and lasting stainless steel, is fully equipped with four flexible hoses and fittings neatly contained in housings, three inbuilt tool trays and a work platform to keep pneumatic tools close at hand.

Clearly, the Alemlube 48010 is the way of the future in helping to prevent back injuries by improving workshop safety, by providing convenience & efficiencies in performing wheel changing operations and ultimately by increasing overall automotive workshop productivity.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Fully Australian Standards approved & compliant

OH&S and Worksafe workshop safety in mind

Minimises manual wheel handling & risk of injury

Helps to easily remove and refit car & light commercial vehicle wheels up to 80kg

Minimum / maximum lifting height 500mm / 1200mm

Minimum / maximum tyre diameter height 490 / 790mm

Manufactured from durable 304 grade stainless steel

Stainless steel rollers support and guide the wheel into position

Perfectly aligns the wheel to the vehicle hub

Pneumatically operated by 2 buttons located on the trolley handles

Supplied complete with an extra Wheel Transport Trolley & Brake Bleeder 10705N

3 handy tool trays and a large work platform for pneumatic tools

Air pressure of 1-5kg/m

Dimensions 760 x 800 x 1200mm (LxWxH). Weight: 64kg



ORDERING INFORMATION:

48010

Tyre and wheel
lifting & handling trolley



When serviced & maintained by Alemlube