



## PRODUCT INFORMATION

August 2015

# 168601

## 400g Air Operated Grease Gun

The 168601 400g air operated grease gun available from Alemlube is a high pressure 60:1 pressure ratio grease gun capable of delivering 1cc of grease each time the trigger is pressed.

The 168601 can be connected to a fixed compressed air line or to the air brake circuit of a commercial vehicle.

Supplied standard with a rigid outlet stem and four jaw coupler, the 168601 can be filled in three different ways - replace the cartridge with a new grease filled 400g cartridge, bulk grease suction or with a grease filler pump.

The 168601 400g air operated grease gun is a solid and reliable performer in all day to day greasing applications where a compressed air line is available and will give years of dependable service in the workshop or on site.



### PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Suits 400g cartridges or bulk filling

High pressure 60:1 pressure ratio

1/4" BSP (f) inlet thread

500cc bulk fill capacity

Three way grease loading

Delivers 1cc of grease per trigger pressing

Connect to a fixed compressed air line or

Connect to a commercial vehicle air brake circuit

Maximum operating air pressure of 145psi (10 bar)

Minimum operating air pressure of 44psi (3 bar)

Supplied standard with a rigid outlet tube and 4 jaw grease coupler

### ORDERING INFORMATION

**168601** 400g Air Operated Grease Gun

