



NEW PRODUCT

INFORMATION

505332 Samoa 20m x 12mm ID Grease Hose Reel



January 2022

The 505332 Samoa 20m x 12mm ID Grease Hose Reel is ideally suited to highly productive markets of mining & construction, railroad & mass transit, manufacturing and applications in service workshops, lube trucks, fleets and truck dealerships.

Supplied standard with 20m of 12mm ID grease hose the 505332's narrow footprint design allows accommodating more reels in available spaces and any method of mounting can be achieved by fixing the hose guide arm in a number of different positions.

Extremely tough construction with the spool mounted on two permanently lubricated and sealed ball bearings effectively reduce the torque load on the spring equating to smooth hose retraction and a longer service life.

A fatigue resistant steel spring delivers years of durable performance resulting in an even load when pulling and recoiling the hose.

The 505332 Samoa 20m x 12mm ID grease hose reel operates with ease facilitated by a large effective radial latching area with the full port shaft and swivel presenting no flow restrictions.

SPECIFICATIONS, FEATURES AND BENEFITS

- Working pressure of 3,988psi (275 bar)
- Inclusive of 20m x 12mm ID grease hose
- 1/2" BSP(f) fluid inlet and outlet
- Full metal heavy duty construction
- Double pedestal design for rigidity & strength
- Full port shaft & swivel
- Large effective radial latching area
- Fatigue resistant steel spring
- Adjustable hose guide arm
- Floor, wall, ceiling or tank mounting possible
- Weight of 39kg
- Also suitable for the transfer of hydraulic fluid

mm (in)	
A	594 (23 3/8")
B	248 (9 7/8")
C	Ø551 (21 3/4")
D	560 (22 1/16")
E	Ø110 (3/8")
F	130 (5 1/8")
G	220 (8 2/3")

