



PRODUCT INFORMATION

May 2013



378702AA

Alemlube Oil Filtration Drum Trolley

The 378702AA Alemlube oil filtration drum trolley has been designed to deliver clean oil filtered to ISO 16/13 Cleanliness levels. Capable of recirculating oil in a “closed-loop” the unit cleans oil that is initially above this level and maintains oil in that condition prior to delivery to your equipment.

The trolley design allows a full 205L drum of oil to be easily loaded into position. Featuring two large solid and two swivel castor wheels, the 378702AA trolley is easily manoeuvred over rough or uneven surfaces and incorporates well-designed supporting brackets and mounts for filtration and transfer equipment.

The 378702AA Alemlube oil filtration drum trolley includes a Samoa 5:1 ratio oil stub pump, Samoa oil hose reel with 10m x ½” hose and Samoa metered nozzle in addition to a non-bypass filter head, drum breather, thermal valve and ¼” FRL + gauge, operating instructions and safety warning decals.

Investment in the Alemlube 378702AA is a smart move towards keeping machine fluids free from outside contaminants and saves money on warranties, reduces downtime and helps maintain productivity.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

- Heavy duty 205L drum trolley
- Samoa 5:1 ratio oil stub pump
- Samoa 10m x ½” oil hose reel
- Samoa metered oil nozzle
- Suction/circulate pick up tube and connectors
- Moisture absorbing drum breather
- Non-bypass filter head
- Filters oil to ISO 16/13 Cleanliness levels
- Four pneumatic wheels
- Oil spill sump with drain
- Filter mounting bracket
- Bunded hose reel platform
- Bunded spill sump
- Keeps fluids free from outside contaminants
- Wooden crate for shipping

ORDERING INFORMATION

378702AA
Alemlube Oil Filtration Drum Trolley

