

NEW PRODUCT

Alemlube

INFORMATION

O300140

5:1 205L Air Operated Oil Pump



September 2019

The Alemlube EL Series O300140 5:1 205L Air Operated Oil Pump is ideal for dispensing oil with a maximum viscosity of SAE240.

An excellent value for money proposition, the EL Series O300140 gives you the opportunity to upgrade from standard hand operated oil drum pumps to a pneumatic solution.

Delivering up to 15L/min the O300140 5:1 205L oil pump is suitable for dispensing motor oil, synthetic oil, hydraulic oil, gear oil and automatic transmission fluid.

Smart design with fewer working parts effectively means less pump wear & tear and facilitates a lower cost of ownership.

Manufactured with efficiency and reliability in mind, the O300140 5:1 205L oil pump is well designed, affordable and is supported by readily available spare parts.

SPECIFICATIONS, FEATURES AND BENEFITS

- Effortless oil transfer
- Smart design with fewer moving parts
- Delivers up to 15L/min
- Maximum operating pressure of 750psi (50bar)
- Maximum oil viscosity of SAE240
- Air consumption of 2.8cfm at 80psi
- 1/2" BSP(m) oil outlet
- 1/4" BSP(f) air inlet connection
- Suction tube length of 940mm, diameter 42mm
- Inlet filter protects against foreign particle contamination
- 2" bung adaptor supplied standard
- Noise level of 82dB
- Saves time and increases productivity
- Low cost of ownership

