



EL SERIES

OWNER'S TECHNICAL MANUAL

HR30000 SERIES Hot Water Hose Reels

Description

The Alemlube EL Series HR30000 hot water hose reels are quality hose handling, retrieval and storage systems with crimped hose end, integral carry handle and detachable mounting bracket enabling 180° hose reel rotation. Manufactured with high density impact resistant and UV stabilised polypropylene cover, EL Series HR30000 hot water hose reels feature a positive latching system that automatically locks the hose at the desired length and the heavy duty internal spring assembly easily retrieves the hose when partially or fully extended.

Suitable for use in the agricultural, automotive, manufacturing, contractor and transport sectors, the HR30000 hot water hose reel increases safety by reducing rewind speed by up to 80%.

Mountable on the wall or ceiling, EL Series HR30000 hot water hose reels feature a constant speed control device ensuring safe and accurate rewinding.

Specifications

Uses	Hot water
Working Pressures	300psi (20bar)
Materials	Polypropylene covers - Hybrid Polymer hose



HR30000 / HR30070 / HR30070C / HR30080 / HR30080C / HR30090

HR30000 SERIES HOSE REELS		
PART No.	PRODUCT DESCRIPTION	PSI/BAR
HR30070	EL Series hot water hose reel complete with 20m x 10mm ID Hybrid Polymer hose and 0.9m lead in hose	300psi/20bar
HR30070C	EL Series hot water hose reel complete with 20m x 10mm ID Hybrid Polymer hose and 0.9m lead in hose & nozzle	300psi/20bar
HR30080	EL Series hot water hose reel complete with 15m x 12mm ID Hybrid Polymer hose and 0.9m lead in hose	300psi/20bar
HR30080C	EL Series hot water hose reel complete with 15m x 12mm ID Hybrid Polymer hose and 0.9m lead in hose & nozzle	300psi/20bar
HR30090C	EL Series hot water hose reel complete with 15m x 12mm ID Hybrid Polymer hose and 0.9m lead in hose & nozzle	300psi/20bar

NSW
TEL: (02) 9677 1555
FAX: (02) 9675 1155

QLD/PNG
TEL: (07) 3204 9166
FAX: (07) 3204 1224

VIC/TAS
TEL: (03) 8787 8288
FAX: (03) 8787 8266

WA
TEL: (08) 9302 4199
FAX: (08) 9303 2095

SA/NT
TEL: (08) 8241 7111
FAX: (08) 8241 7011

NZ
TEL: (64) 9 447 1007
FAX: (64) 9 447 1008



Specifications for HR30070 / HR30070C / HR30080 / HR30080C / HR30090C



Item	Max Pressure (psi/bar)	Hose Working Temperature (C)	Hose Working		
			Material	I.D. (inch/mm)	Length (m/ft)
HR30070	300/20	-40° to +80°	Hybrid Poylmer	3/8" BSPT / 10	20 / 65
HR30070C	300/20	-40° to +80°	Hybrid Poylmer	3/8" BSPT / 10	20 / 65
HR30080	300/20	-40° to +80°	Hybrid Poylmer	1/2" BSPT / 12	15 / 49
HR30080C	300/20	-40° to +80°	Hybrid Poylmer	1/2" BSPT / 12	15 / 49
HR30090C	300/20	-40° to +80°	Hybrid Poylmer	3/4" BSPT(F) / 19	15 / 49
				1/2" BSPF(M)	

NSW
TEL: (02) 9677 1555
FAX: (02) 9675 1155

QLD/PNG
TEL: (07) 3204 9166
FAX: (07) 3204 1224

VIC/TAS
TEL: (03) 8787 8288
FAX: (03) 8787 8266

WA
TEL: (08) 9302 4199
FAX: (08) 9303 2095

SA/NT
TEL: (08) 8241 7111
FAX: (08) 8241 7011

NZ
TEL: (64) 9 447 1007
FAX: (64) 9 447 1008