



PRODUCT INFORMATION

October 2013



51095P

Diesel Fuel Preset Bowser with Pedestal

The 51095P preset diesel fuel bowser with pedestal is a multi-user product designed to cater for the market demand for a dispensing unit complete with a pump, flow meter and automatic nozzle.

Capable of flow rates of up to 70 L/min the 51095P diesel fuel bowser is easily interfaced with sophisticated fleet management systems and can be connected to an external electronic system and be enabled for dispensing to switch the pump on or off. During dispensing it sends calibrated pulses to the electronic system produced by the pulse meter fitted inside the dispenser. Connection to a level switch is also possible in order to automatically switch off the pump in the event of a low tank level.

The 51095P preset diesel fuel bowser with pedestal is highly accurate and operates continually with a low noise level and is also available as the bowser cube only without the pedestal as shown here.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Automatic nozzle with flow rates of up to 70 L/min

Preset functionality

Can be interfaced with fleet management systems

Accurate to $\pm 0.5\%$

Continuous operation with IP55 protection

Hose length of 4m

240V, voltage 850 Watt, Amp. max 4.2

Accessories available on request:

Kit of 10 user keys

Wall support kit

Water captor filter

Kit lock

2" quick coupling

2" drum connector

Also available 51095 without pedestal

ORDERING INFORMATION

51095P

Diesel Fuel Preset Bowser with Pedestal

51095

Diesel Fuel Preset Bowser Cube Only

