

NEW PRODUCT



INFORMATION

G10005

EL Series Quick Connect Grease Coupler



June 2021

The Alemlube EL Series G10005 quick release grease gun coupler is a game changing patented lock-on grease gun coupler with a lever action and sliding sleeve that securely locks the coupler onto a grease nipple creating a leak proof seal that has taken the market by storm.

Hands-free greasing is now a reality!

Lock the G10005 onto a grease nipple simply by depressing the trigger, attaching and releasing the trigger for a tight fit. No hands are needed to align the coupler or keep it on the grease nipple.

Leak proof greasing - even at extreme angles

Once the G10005 is attached, greasing can be performed at pressures of up to 10,000psi (690bar) with a burst pressure of 15,000 (1,034bar) and can be forced to extreme angles on the grease nipple without leaking.

Activate the trigger to disengage - easy release

Simply pressing the trigger releases the coupler from the grease nipple.

SPECIFICATIONS, FEATURES AND BENEFITS

- Works with all grease gun types - pneumatic, manual & battery
- Kink-free swivel connector
- Intergrated one-piece jaws
- Extreme slim nose with valid length
- Maximum working pressure of 10,000psi (690bar)
- Burst pressure of 15,000psi (1,034bar)
- Fits all metric and SAE specification grease nipples
- 4 jaw hydraulic connector with securing sleeve
- Lock-on & free up both hands to operate your trigger or level action grease gun
- Eliminates hydraulic lockout
- Easy disconnection regardless of hydraulic pressure build up in the line
- Patented Design
- Light weight at just 113g
- 90mm in length
- 1/8" BSP(f) thread
- Suitable for high pressure, heavy duty greasing applications

www.alemlube.com.au



www.alemlube.co.nz

NSW/ACT (02) 9677 1555

QLD/PNG (07) 3204 9166

VIC/TAS (03) 8787 8288

WA (08) 9302 4199

SA/NT (08) 8241 7111

NZ (09) 447 1007