



PRODUCT INFORMATION

SEPTEMBER 2018



P50

Alemlube Petrol Driven 2" Diesel & Water Transfer Engine Pump

The Alemlube P50 petrol driven 2" transfer engine pump is specifically designed and manufactured for the transfer of diesel and water. Mounted in a robust tubular steel roll frame with rubber feet the P50 is completely portable, suits many industrial, workshop, agricultural, municipal, marine services and on site applications including construction site dewatering and is capable of transferring up to 600 litres of diesel fuel or water per minute.

Driven by a powerful OHV 4 stroke air cooled petrol engine this lightweight die-cast aluminium pump with 2" diameter inlet & outlet ports operates efficiently with a maximum suction head of 8 metres and a maximum lift head of 28 metres.

Always ready to perform tank filling, diesel or water transfer the P50 has a 3.6L fuel tank capacity with a manual starting system.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

- Flow rates of up to 600L/min
- 6.5HP (3,600rpm) air cooled 4-stroke petrol engine
- 2" (50mm) inlet/outlet
- Maximum suction head of 8m
- Maximum lift head of 28m
- Fuel tank capacity of 3.6L
- Oil tank capacity of 0.6L
- Completely portable with pull start

ORDERING INFORMATION

P50 Alemlube Petrol Driven 2" Diesel & Water Transfer Engine Pump

