



PRODUCT INFORMATION

JUNE 2018



PR80

Alemlube Petrol Driven 3" Diesel & Water Transfer Engine Pump

The Alemlube 3" PR80 petrol driven transfer engine pump is specifically designed and manufactured for the transfer of diesel and water. Mounted in a robust tubular steel roll frame with rubber feet the PR80 is completely portable, suit many industrial, workshop, agricultural, municipal, marine services and on site applications including construction site dewatering and are capable of transferring up to 1000L/min of diesel fuel or water per minute.

Driven by a powerful OHC 4 stroke air cooled petrol engine these lightweight die-cast aluminium pumps are fitted with 3" diameter inlet & outlet ports that operate efficiently with a maximum suction head of 8 metres and a maximum lift head of 32 metres.

Always ready to perform tank filling, diesel or water transfer the PR80 has a 3.8L fuel tank capacity with a manual starting system.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

- Flow rates of up to 1,000L/min
- 3.5HP (3,600rpm) air cooled 4-stroke petrol engine
- 3" (80mm) inlet/outlet
- Maximum suction head of 8m
- Maximum lift head of 32m
- Fuel tank capacity of 3.8L
- Oil tank capacity of 0.6L
- Completely portable with pull start

ORDERING INFORMATION

PR80 Alemlube Petrol Driven 3" Diesel & Water Transfer Engine Pump

